STERLING LIGHTING

Project Name

Luminaire Type

SL11 Archer Light



Product Features

- Single source LED chips for greater lux control
- Made with Marine-Grade, Virgin Brass
- Comes with screws for mounting
- Ultra-durable, frosted glass lens to reduce glare

Specifications

Rev. 08/2026

LuminaireType: Integrated Low Voltage LED
Color Temperature: 2700K / 3000K
Material: Marine-Grade, Virgin Brass with a UV coating
Finish: Antique Bronze or Raw Brass
Wattage: 3.7W - 6.8W
Field Angle: 59°

Lumen Output: 219 lm
Operating Voltage: 9V - 15V AC
Light Source: CREE LED
Optics: 24°, 40° (standard), 60°, and 80° (no optic)
Color Rendering Index: 96+
TM-30 Rf: 95
TM-30 Rg: 101

Wire Lead: 10' 18AWG
Mounting: Comes with 2 self-tapping machine screws and 2 wood screws
Lens: Frosted Lens
Listing: ETL, FCC
Standard: UL 1838
Rating: IP65

Product Drawings



Driver at 15V Input

Settings	Lumens	VA	Lm/W
Low	219 lm	5.51 VA	58.47

STERLING LIGHTING

Nom du projet

Type de luminaire

SL11 Archer Light



Caractéristiques du produit

- Puce LED à source unique pour un meilleur contrôle de l'éclairement (lux)
- Fabriqué en laiton vierge de qualité marine
- Vis de fixation incluses
- Lentille en verre dépoli ultra-résistant pour réduire l'éblouissement

Caractéristiques

Rev. 08/2026

Type de luminaire : LED basse tension intégrée
Température de couleur : 2700 K / 3000 K
Matériau : Laiton vierge de qualité marine avec revêtement anti-UV
Finition : Bronze antique ou laiton brut
Puissance : 3,7 W – 6,8 W
Angle de champ : 59°

Flux lumineux : 219 lm – 360 lm
Tension de fonctionnement : 9 V – 15 V CA
Source lumineuse : LED CREE
Optiques : 24°, 40° (standard), 60° et 80° (sans optique)
Indice de rendu des couleurs : 96+
TM-30 Rf : 95
TM-30 Rg : 101

Câble de raccordement : 10 pi, calibre 18 AWG
Montage : Fourni avec 2 vis autotaraudeuses pour métal et 2 vis à bois
Lentille : Givrée
Homologations : ETL, FCC
Norme : UL 1838
Indice de protection : IP65

Dessins du produit



Pilote pour entrée 15 V

Paramètres	Lumens	VA	Lm/W
Élevé	360 lm	9.67 VA	52.69